



Tree Guying Specifications: ATG-R/ATG-HD


For up to 4" Caliper Trees
 (3) Polypropylene guylines 3/4" X 12'=800 lb test, olive drab, UV resistant
 (3) Nickel plated spring cam-lock tension clips
 (3) Arrowhead Nylon Anchors (4" X 3-3/4")
 or
 (3) Arrowhead Metal Anchors for hard soil (4" X 3-3/4")

Tree Guying Specifications: ATG-J

For up to 7" Caliper Trees
 (3) Polypropylene/Polyester guylines 1" X 12'=1,000 lb test, olive drab, UV resistant
 (3) 1-1/4" Nickel plated, non-rusting spring cam-lock tension clips (1,500 lb break strength)
 (3) Arrowhead Aluminum Anchors for any soil type (5-1/2" X 4-1/2")

ArborAnchor[®]

ArborAnchor driven below grade to necessary depth determined by soil. (1.5 to 2.5 feet as required)



GUY LINE

NEW PLANTING SOIL BACKFILLED TO CREATE WATERING RING


NO MULCH NEAR TRUNK

3 INCH LAYER OF MULCH

EXISTING SOIL

Tension Buckle

Loop loose end of webbing around leading branch of tree. Tie 1/2 knot onto backside of buckle. Pull buckle towards ArborAnchor to tension line.



PLANTING HOLE 2X DIAMETER OF ROOTBALL